Cleaner for Wood-Plastic-Decking (WPC)

Technical Data Sheet January 2020 Page 1/1





» cleans decking of wood/plastic composite quickly and thoroughly

Product characteristics:

SAICOS Cleaner for Wood-Plastic-Decking (WPC) for the simple and thorough cleaning especially of WPC- (wood/plastic-composite) decking. Low in solvent, chlorine-free, formaldehyde-free, does not contain bleaching agents, biologically degradable.

Article number:

8123

Fields of application:

For the simple and thorough cleaning especially of WPC-(wood/plastic-composite) decking.

Preperation:

Mix SAICOS Cleaner for Wood-Plastic-Decking (WPC) 1:10 with water (e. g. 0,5 liter – concentrate in 5 liters of water).

Processing:

Apply dilution evenly with srubbing brush on the WPC decking (do not leave pools on surface). Leave to act for 5 -20 min. Re-treat spots dried during that time.

Remove dissolved dirt with wiper, grooves may be cleaned with a srubbing brush.

Wipe afterwards 2–3 times with clear water.

Coverage per litre:

1 liter of SAICOS Cleaner for Wood-Plastic-Decking (WPC) dilutet with 10 liters of water adds up to 11 liters cleaning dilution (depending on dilution and grade of dirt).

Number of treatment: 1x, if heavily soiled 2x

Drying time:

Dependant on water condition; dries as usual wet surface.

Cleaning of tools:

Thorougly with plenty of water.

Storage:

In closed container unlimited.

The liquid product is susceptible to frost. Transport and store frost-protected (> 5 °C).

Physical properties:

Density: 0.995 - 1.023 g/cm³

Odour: faint /mild, odourless when dry

Flashpoint: not flammable

Safety Instructions – First Aid:

Keep out of the reach of children. Do not fill into food, beverage or other containers used for foodstuffs. Causes serious eye irritation. Wash hands thoroughly after handling. Wear protective gloves and eye/face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: get medical advice/attention.

GGVSEB / ADR -/-

Our application advice is provided to the best of our knowledge and based on experiments, however, applies only as a non-binding recommendation and does not exempt you from testing the products supplied by us as to their suitability for the intended purpose. Since the application and processing of the products is beyond our control, the responsibility rests solely with the user. With publishing a new technical data sheet the previous loses its validity.

SAICOS COLOUR GmbH

Carl-Zeiss-Str. 3

D-48336 Sassenberg

4 +49 2583 3037-0

♣ +49 2583 3037-10

info@saicos.de

www.saicos.de