

Ecoline Slip Resistant "R10"

Technical Data Sheet

March 2020

Page 1/1



Ecoline



- » *supplement for our Ecoline MultiTopPlus System for increasing of slip resistance*
- » *just in combination with Ecoline Hardener 2K*

Product characteristics:

By combination with supplement *Ecoline Hardener 2K* you receive an improved slip resistance. Also on top of *Ecoline Oil Ground Coat / SAICOS Oil Ground Coat*.

DIBt approval: Z-157.10-162.

Slip Resistant R10.

Article number:

9916Eco

Fields of application:

For shaking into *Ecoline MultiTop*.

Due to the additional component *Ecoline Hardener 2K* and *Ecoline Slip Resistant "R10"*, other coating properties might be influenced. When in doubt, make a test coating. The following standards are recommended to take note of: DIN 18356 „Working with parquet“ and DIN 18367 “Working with wooden paving”.

For all wood floors (hardwood floors, parquet and multilayer flooring), bamboo and other interior wooden surfaces.

Furthermore, in combination with different primers (*Ecoline Oil Ground Coat / SAICOS Oil Ground Coat / Ecoline Future Universal Ground Coat*) suitable for hardwoods, exotic and thermally treated wood. Please make a trial coating in case of having doubts. For further technical information please see the technical data sheet *Ecoline MultiTop Plus System*.

Processing:

Fill supplement into *Ecoline MultiTop* lacquer and shake well two minutes. Let rest for 5 minutes, re-shake and apply rapidly with *SAICOS Aqua Roller*.

Coverage:

Application with *SAICOS Aqua Roller*,

Application quantity 100 - 120 g / sqm.

0.45 liter of supplement for 4.55 liter *Ecoline MultiTop*.

5 liters are sufficient for about 45 sqm (one coat).

Coverage depends on wood species and surface structure.

Storage:

In unopened / sealed container at least 6 months.

The liquid product is susceptible to frost. Frost-free transport and store (> 5 ° C).

Safety - First Aid:

Keep out of the reach of children. Do not fill into food, beverage or other containers used for foodstuffs.

Contains: TMDD.

May produce an allergic reaction.

Safety data sheet available on request.

EU limit for two component lacquer (Cat A/j): 140 g / l (2010)
SAICOS Ecoline MultiTop with supplement *Ecoline Slip Resistant "R10"* contains max. 140 g / l VOC.

Our application advice is provided to the best of our knowledge and based on experiments, however, applies only as a non-binding recommendation and does not exempt you from testing the products supplied by us as to their suitability for the intended purpose. Since the application and processing of the products is beyond our control, the responsibility rests solely with the user. With publishing a new technical data sheet the previous loses its validity.

SAICOS COLOUR GmbH

Carl-Zeiss-Str. 3

D-48336 Sassenberg

☎ +49 2583 3037-0

☎ +49 2583 3037-10

✉ info@saicos.de

www.saicos.de