



Dear customer

Would you like to paint, beautify or maintain your wood? The coating should dry fast, be easily applied and last for a long time? Then SAICOS always has the right product for you.

When developing our products we have taken all your wishes and processing aids into account so that you can treat your wood as simple as possible.

Via a QR-Code directly on the product itself or at the shelf in a specialist shop you can either click on the technical data sheet or a video with step-by-step explanations. The QR-codes functions are: helping with the actual buying decision at the shelf, watching the product video at home or as a virtual instruction manual on your 'building site'.

For the new year we've taken all your wishes into account and expand our coating product range.

Curious? Discover more on the following pages.

Thank you very much for your trust.

Your SAICOS team

	Introduction	page	2
	SAICOS QR-Code	page	4
	Floor coatings		
	Premium Hardwax-Oil	page	6
	Premium Hardwax-Oil Additives	page	7
	Single Top Oil (2K)	page	8
NEW)	Single Top Oil System (Additives Hardener 2K, Oil Care)	page	9
	Ecoline Hardwax-Oil 2.0, Additive Hardener 2K	page	11
	Ecoline Hardwax-Oil	page	12
	Ecoline Oil Ground Coat	page	13
	Ecoline MultiTop ^{Plus} lacquer system	page	14
	Ecoline MultiTop Zusätze	page	15
	Ecoline Ground Coat 'Speed'	page	16
	Ecoline Crack-Filler	page	17
	Wood Impregnation biocide-free	page	18
	Ground Oil Extra Thin	page	19
	2K PU Elastic	page	20
	2K PU system additives, Basic Cleaner Concentrate	page	21
	zivi o system additives, pasie ciedne. Concentidate	page	
	Interior wood coatings		
	Color Wax	page	22
	UV Protective Wood Finish Interior, Worktop-Oil	page	23
	Furniture Oil	page	24
	Turniture on	page	27
	Tools	nage	25-27
	10013	page	25 21
	Cleaning, care & accessories		
	Ecoline Wash Care	page	29
	Ecoline Magic Cleaner	page	30
	Wax Care, Ecoline Wax Care	page	31
	Ecoline Floor Care Set und Clean & Care Set	page	32
	Wash Care Oil white, Professional Care Oil white	page	33
NEW	Stain Remover	page	35
	Ecoline MultiTop Lacquer Polish, Ecoline Refresher	page	36
	Telescope-Maintenance Cloth, Ecoline Maintenance-Set	page	37
	Care instructions		
	for oiled wood surfaces	page	38
	für lackierte Holzoberflächen	page	44
	for laminate, vinyl and design floors	page	48
	All care products at a glance	page	50
	p a. a. g.a	۳۳9۰	50
	FAO	nage	52
	17194	page	52

The QR-Code from SAICOS

product application clearly arranged



· Our service for you:

- A technical data sheet as well as a self-explanatory application video per product is available.
- Application video: the correct application with vivid step-by-step explanations.
- Technical data sheet: all that there is to know via a PDF can be clicked on either directly at the shelf or via can label.



A superior coating

for permanently beautiful surfaces





easy to apply

DIBt approval Z-157.10-4

$I = 14 \, \text{m}^2 \, (2 \, \text{coats})$















3305 Matt

colourless

3308 Frost transparent matt

Rosewood transparent matt

3200 Satin matt colourless

page 26.

touch.

re-oiled at any time.

3317 Silver Grey transparent matt

opaque ultra matt

0,125 I

0,75 I

2,5 I

10 I

25 I

For natural, permanently beautiful surfaces that are easy to maintain, we recommend our SAICOS Premium Hardwax-Oil.

The natural ingredients of the hardwax-oil

penetrate deeply into the pores of the wood and give the surface a wonderful

Surfaces coated with SAICOS Premium Hardwax-Oil can be sanded and partially

No visible contact points and all naturally based, suitable for all wood surfaces. Suitable tools such as the Oil/Wax-Roller, Universal-Roller, etc. can be found on

(Item Number) 100

(Item Number) 300

(Item Number) 500

(Item Number) 700

(Item Number) 800



3328 Teak transparent matt

3333 transparent ultra matt

Ultra matt Plus colourless

3100 White transparent matt

3381 Walnut transparent matt

The Premium Hardwax-Oil System

3 additives that are particularly designed for your needs



Additive UV Protection (3242)

Natural discoloration is a direct result of the wood's exposure to light.

The colourless *Premium Hardwax-Oil* including *Additive UV Protection* reduces the natural discoloration of the wood significantly.



Additive Anti-Slip R10 (3240)

We can fulfill a big market demand with the colourless *Premium Hardwax-Oil* including *Additive Anti-Slip*. The final coating achieves the certified anti-slip property R10.



Additive Hardener 2K (3243)

With the Additive Hardener 2K, the colourless SAICOS Premium Hardwax-Oil dries quicker even under difficult working conditions e.g. high air humidity.

In general, coated surfaces can be walked on earlier and have an improved abrasion hardness.

The additive can also be used for the Ecoline Oil Ground Coat and Ecoline Hardwax-Oil (3600Eco).

The new Single Top Oil - System

for natural, beautiful surfaces







Single Top Oil (2K)

Can Size	ltem Number
0,125 L	(Item Number) 100
0,375 L	(Item Number) 200
0,75 L	(Item Number) 300

This product line is characterized by a single application, natural color shades and a good dirt resistance. Suitable for wooden floors, furniture, worktops, etc. in private living areas.

Can only be used in combination with Single Top Hardener 2K (4643). This must be ordered separately (page 9).

just one coat

DIBT approval: Z-157.10-4

1 L = approx. 65 m² (1 coat)



















4615 Off White transparent

4610 Colourless transparent

4616 Nature transparent

4612 White Oak transparent

Deep Brown

4614 Fog transparent

Old Brown transparent

The new Single Top Oil - System

for natural, beautiful surfaces

The new Single Top Oil system

The new Single Top Oil (2K) system is a high-quality one-layer system for private living areas. Adding the Single Top Hardener 2K results in a high-quality, easy-care surface. For an optional additional protection, we offer the Single Top Oil Care that can be applied as an initial care.





Additive Single Top Hardener 2K

Can Size	Item Number
for 0,375 L	4643 055
for 0,75 L	4643 157

Simply pour into the *Single Top Oil (2K)*, stir well and you are ready to go!

The quantity of the *Single Top Hardener 2K* is matched to the respective tin size of the *Single Top Oil (2K)*.

Single Top Oil (2K) must always be used in combination with Single Top Hardener 2K.





dirt-repellent $1 L = 100 \, \text{m}^2 \, (1 \, \text{coat})$

Single Top Oil Care











Can Size Item Number
1 L (Item Number) 404

4639 Matt colourless **4640** *White*transparent matt

Single Top Oil Care has especially been developed for the initial care, renovation and refreshment of SAICOS Single Top Oil (2K) surfaces. The surface is easy to clean, water-repellent and hard-wearing.

Ecoline Hardwax-Oil 2.0

Zerø VOC · 100 % Ecological



The ecological update For the healthy living coating

Ecoline Hardwax-Oil 2.0

Zerø VOC · 100 % Ecological





Ecoline Hardwax-Oil 2.0

Zerø VOC · 100 % Ecological

Can Size	Item Number
0,125 L	3620Eco 100
0,75 L	3620Eco 300
2,5 L	3620Eco 500
10 L	3620Eco 700

Ecoline Hardwax-Oil 2.0 combines quality and ecology.

Based on natural oils and waxes, it creates a natural and durable surface and is especially suitable for heavily used wood surfaces.

The product is applied by spatula and afterwards buffed with white or beige pad. The surface is slip-resistant R9, healthy living and open-pored.

It also allows an easy maintenance with aligned *SAICOS* care products.

easy to apply

DIBt approval Z-157.10-4

$1 L = 35 m^2 (2 coats)$

















3620Eco + 3643Eco Satin matt (2K) colourless





Additive Hardener 2K (3643Eco)

Can Size	Item Number
for 0,75 L	3643Eco 055
for 2,5 L	3643Eco 155

With the Additive Hardener 2K the Ecoline Hardwax-Oil 2.0 gets a higher resistance.

In general, coated surfaces can be walked on earlier and have an improved abrasion resistance.

For your green footprint

our innovative and eco-friendly coating system



low-solvent: VOC < 10 %

DIBt approval Z-157.10-4

 $1 I = 35 \text{ m}^2 (2 \text{ coats})$















3600Eco Satin matt colourless

Ecoline Hardwax-Oil – satin matt colourless

Item Number
3600Eco 100
3600Eco 300
3600Eco 500
3600Eco 700

If you want to achieve permanently beautiful, natural surfaces that are easy to care, whilst avoiding solvents, we recommend our Ecoline Hardwax-Oil.

The natural ingredients of the hardwax-oil penetrate deeply into the pores of the wood and give the surface a wonderful haptic and satin matt appearance.

It dries quickly, giving you a high-class surface in just one day.

Surfaces coated with *Ecoline Hardwax-Oil* can be sanded and partially re-oiled at any time. No visible contact points and all naturally based, suitable for all wood surfaces.

Also usable with Hardener 2K (3243).



Free choice of final coating

get beautiful wood thanks to the best natural oils



low-solvent: VOC < 10 %

DIBt approval Z-157.10-4

$1 I = approx. 65 m^2 (1 coat)$















Ecoline Oil Ground Coat

Can Size	Item Number
0,125 L	(Item Number) 100
0,75 L	(Item Number) 300
2,5 L	(Item Number) 500

Highlight the beauty of your wood with pure natural oil - low-solvent. High-pigmented, for professional usage.

The Ecoline Oil Ground Coat has been especially developed for wood, cork and bamboo floors, as well as particularly heavily used pieces of furniture.

It combines an exceptional good abrasion resistance with high durability and emphasises the natural beauty of your wood.

For the final coat, we recommend:

- » SAICOS Hardwax-Oils or
- » Ecoline MultiTop^{Plus} lacquer system

Also usable with Hardener 2K (3243).

3408Eco *Extra-White* transparent 3409Eco White transparent

t t

3410Eco Colourless transparent 3413Eco Birch transparent

3417Eco Silver Grey transparent 3418Eco Pear transparent 3422Eco Chestnut transparent

3428Eco *Teak* transparent

3438Eco *Mahogany* transparent 3458Eco Oak transparent 3474Eco Basalt Grey transparent **3477Eco Graphite**transparent

3479Eco Antique Grey transparent **3481Eco** *Walnut* transparent **3485Eco** *Rosewood* transparent **3490 Eco Ebony** transparent



Ecoline MultiTop^{Plus} – the plus for a perfect floor

MultiTop: one lacquer and many possibilities

MultiTop 1 K lacquer is the perfect choice for surfaces with extremely high demands in the residential sector. It can also be used without a primer.





low-solvent: VOC < 10 %

DIBt approval Z-157.10-162*

$1 l = approx 9 m^2 (1 coat)$

9980Eco 9985Eco
Ultramatt Matt
colourless colourless

9990Eco 9995Eco
Satin matt High gloss
colourless colourless

* The DIBt approval is also valid in combination with each of the 7 additives.

Ecoline MultiTop

Econne mannop				
Ca	ın Size	lte	m Numbe	
	4,55 l	(Item Nu	ımber) 61	
interior	9m ²	application	transparent	
R9 slip resistant	ecologically friendly	DIN EN 71-3		

Suitable tools such as the aqua roller, etc. can be found on page 26.



Add additive to the laquer, shake well and the coating is ready for use.



All possible combinations at a glance:

	Hardener 2K	UV Protection	Extra White	"R10"	Pitch Black	"Slow Down"	Pure
MultiTop	✓	✓	✓	✓	✓	✓	✓
Hardener 2K		✓	✓	✓	✓	✓	✓
UV Protection	✓		✓	✓	✓	✓	✓
Extra White	✓	✓		✓		✓	
"R10"	✓	✓	✓		✓	✓	✓
"Slow Down"	✓	✓	✓	✓	✓		✓
Pitch Black	✓	✓		✓		✓	
Pure	✓	✓		✓		✓	

The Ecoline MultiTopPlus System

7 new supplements for endless varieties



Hardener 2K (9908Eco)

With the Additive Hardener 2K the Ecoline MultiTop dries faster, especially under difficult conditions such as high humidity. Generelly, the surface has a higher abrasion resistance and can be walked on earlier.



UV Protection (9914Eco)

Significantly reduces the natural colour changes of wood.







Information

Extra White (9915Eco)

For an extra-white floor, we recommend combining with Ecoline Oil Ground Coat 3408Eco.



objects like old people's homes.










Delayer 'Slow Down' (9919Eco)

Extends the workability of the lacquer, especially under critical site conditions with high temperatures and low humidity.



One can accomplish a black surface with extraordinary effect. The structure of the wood and the laying system is still visible.









Pure (9933Eco)

When rolling the Ecoline MultiTop a perfectly protected wood surface can be achieved that looks as if untreated.

Special solutions

to complete our lacquer system



DIBt approval Z-157.10-162

1 I = approx. 15 m² (1 coat)











Ecoline Ground Coat 'Speed' - colourless

Can Size	Item Number
51	9912Eco 610

Ecoline Ground Coat 'Speed' is a product especially developed for wood, bamboo and all common types of wood.

The primer is healthy for living, breathable and complies with the VOC guidelines 2010. It is easy to apply and can be **overpainted after only 60 minutes.**

With a firing effect.





$1 L = approx. 12 m^2$











Ecoline Crack-Filler - colourless

Can Size	ltem Number
51	0970 002Eco 610

Ecoline Crack-Filler is water-based for simply producing grout from grinding dust.

It dries extremely quickly and has impressive sanding properties.

Suitable for all *SAICOS* floor primers and coatings, as well as all common wood types that are dry and uncoated.

Application quantity: 80 - 100 g/m².



Our alternative for biocide wood protection

particularly recommended for wood in moist rooms



protection from moisture

1 I = approx. 8 m² (1 coat)









Wood Impregnation biocide-free

Can Size	Item Number
0,125 L	9000 100
0,75 L	9000 300
2,5 L	9000 500
10 L	9000 700
25 L	9000 800

SAICOS Wood Impregnation biocide-free is totally free of organic biocides and therefore particularly harmless.

It provides natural protection against moisture damage, penetrates deeply into the wood and keeps it elastic. The wood can still breath, allowing the moisture to escape.

Particularly recommended for treating woods in moist rooms like bathrooms and kitchens, which are at risk of blue stain. The alternative to biocide or fungal wood protection treatments.

This is not a stand-alone finish. A final coat must be applied within 1 week. We recommend SAICOS Color Wax or SAICOS Premium Hardwax-Oil.



Special treatment for exotic woods

with our particularly deep-penetrating Ground Oil



especially for exotic woods

DIBt approval Z-157.10-4

 $1 I = 17 \text{ m}^2 (1 \text{ coat})$











Ground Oil Extra Thin

Can Size	ltem Number
0,125 L	(Item Number) 100
0,75 L	(Item Number) 300
2,5 L	(Item Number) 500
10 L	(Item Number) 700
25 L	(Item Number) 800

SAICOS Ground Oil Extra Thin is an open-pored primer that penetrates deeply and easily and is recommended as first coat for exotic and hardwoods.

Floors treated with SAICOS Ground Oil Extra Thin and SAICOS Premium Hardwax-Oil repel dirt and water and are extremely resistant. Moisture cannot harm this open-pored coating.

For the final coat we recommend:

» SAICOS Premium Hardwax-Oil



Waterborne 2K PU-coating

to renovate PVC, Linoleum and design floor





restoration instead of exchange

DIN 68861 - Part 1

DIBt approval Z-157.20-208*

$1 L = 10 m^2 (1 coat)$

* The DIBt approval is also effective in combination with each of the supplements.















2K PU Elastic

Can Size	Item Number
4,55 L	9600 618

Waterborne 2K PU sealer based on polyurethane to renovate surface protection and to be used as a new coating on design floors, PVC and Linoleum.

This hard-wearing coating offers a very good adhesion as well as high elasticity. It is highly resilient and abrasion-resistant and offers a better resistance against common household disinfectants.

Due to its excellent leveling SAICOS 2K PU Elastic is easy and safe to use. The high solid content reduces dirt-attraction and reduces maintenance efforts.

Can only be used in combination with Hardener 2K (9608). This has to be ordered separately.

9600 Matt colourless



Waterborne 2K PU-coating

individual additives and cleaning products





Hardener 2K (9608)

By adding the *Hardener 2K* the surfaces dries quicker – especially under difficult conditions e.g. high humidity.

2K PU Elastic must always be used in combination with Hardener 2K.

Anti-Slip R10 (9616)

The supplement Anti Slip R10 fulfills a common request for commercial projects. Especially suitable for staircases, projects or surfaces with higher anti-slip properties.









Delayer (9619)

Prolongs the workability of the 2K PU Elastic. Especially suitable for critical conditions on-site (higher temperatures and low humidity).

All possible combinations at a glance:

	2K PU Elastic	Anti-Slip R10	Delayer
Hardener 2K	✓	✓	✓
Anti-Slip R10	✓		✓
Dolavor	1	✓	





for all water-resistant, alkali-sensitive floor coverings

removes hardest coatings

Basic Cleaner Concentrate

Can Size	Item Number
1 L	8124 409

SAICOS Basic Cleaner for design flooring, PVC & linoleum is a concentrated intense cleaner for all water-resistant, alkali-sensitive floor coverings. Especially for design floors, PVC and linoleum. Also suitable for natural- or artificial stone, limestone, clay, brick and natural rubber. Also removes strongest dirt.

The use saves time due to its short exposure time. Loosened dirt is easy to remove.

Also suitable for cleaning machines.

We recommend to use a green pad (0950 599).

New life for your favorite furniture

and colourful highlights for walls and floors





DIN EN 53160

DIBt approval Z-157.10-4

$I = approx. 21 \text{ m}^2 (1 \text{ coat})^*$















3009 White transparent

3018

Pear transparent

Walnut transparent

Lemon Yellow opaque

4009 White opaque

3010 Colourless transparent

3028 Teak transparent

Rosewood transparent

Raspberry opaque

Black opaque

Color Wax

Can Size	Item Number
0,125 L	(Item Number) 100
0,375 L	(Item Number) 200
0,75 L	(Item Number) 300
2,5 L	(Item Number) 500

The natural oils used for SAICOS Color Wax penetrate deeply into the wood and keep it elastic. Natural waxes protect the surface and ensure high durability and ease care. Perfect for children's toys and all wooden objects.

Ideal for restoring old furniture:

gives new life to surfaces, making them both resistant and easy to maintain.

SAICOS Color Wax is excellent for designing colourful wall surfaces and floors made of wood, bamboo and cork. On heavily used wood surfaces (e.g. flooring), we recommend using SAICOS Premium Hardwax-Oil as a final coating.

> 3017 Silver Grey transparent

> > 3058 Oak transparent

Ebony transparent

3033 Pink opaque Vintaae Blue opaque

*Opaque:

3013

Rirch

3032

Cherry

transparent

transparent

1 L = approx. 12 m² (2 coats)



prevents yellowing

1 l = approx. 9 m² (2 coats)















7701 Colourless transparent 7704 White transparent

UV Protective Wood Finish Interior

Can Size	Item Number
0,125 L	(Item Number) 101
0,75 L	(Item Number) 301
2,5 L	(Item Number) 501

Transparent wood finish for interior woods. Get a natural 'untreated' effect whilst retaining outstanding protection against yellowing and a neat, dirt-repellant surface.

Can only be painted over with the same coating or with SAICOS Bel Air H₂O Garden- and cladding colour.



Simple application

1 L = approx. 14 m² (3 coats)

Food safe acc. EN 1186















Worktop Oil

Can Size	Item Number
0,125 L	3355 100
0,5 L	3355 403

SAICOS Worktop Oil is a special oil finish developed according to the latest research to provide a durable, hardwearing natural surface with a quick drying time.

Penetrating deeply into the wood, SAICOS Worktop Oil protects from the inside, retaining the wood's elasticity, whilst natural waxes protect the surface and ensure high durability.

3354 Frost colourless matt 3355 Matt colourless

Cleaning, care & accessories

to make correct care a child's play





Furniture Oil – colourless

Can Size	Item Number	
0,3 l	3311 180	
Presentation box with 20 cans		
031	3300	

SAICOS Furniture Oil has been specially developed for treatment of furniture surfaces, tables and doors and other wooden objects (e.g. wooden toys) in the home.

It is easy to apply, very resistant and repels water and dirt.

SAICOS Furniture Oil bonds permanently with the wood, therefore no sanding is required in the event of a renovation. It retains the natural beauty, even after years.

water-resistant effect

$0.3 I = approx. 7 m^2 (1 coat)$















3311 Colourless transparent

Our Easy Paint Set

For perfect application of SAICOS coatings





Everything for the perfect application

from Flat Brush to Abrasive Fleece Mat









Size	ltem Number
150 mm	0950 150
220 mm	0950 220

Abrasive Fleece Mat

renovation pad marone, 410 mm, grain 280

Colour	Item Number
Marone	0950 727

Roller, 250 mm



Item Number
0950 008
0950 013

Super Pad (16" / 406 mm)

Colour	Item Number
white	0950 575
green	0950 599
black	0950 623
beige	0950 583
beige	0950 585

Thoughtful & approved tools

to make your work easier

Brush Cleaner - benzene-free

Can Size	Item Number
11	5100 404
101	5100 715

Cleans tools after use with oil / wax-based SAICOS wood finishes. Also removes resins.

especially low-odor

thoroughly & carefully





Double Blade Scraper stainless steel



Size	ltem Number
270 mm	0950 027

Flat Brush for oil and water systems



Size	Item Number
30 mm	0950 030
50 mm	0950 050
60 mm	0950 060
100 mm	0950 100

Telescopic handle with click connection

High-quality processed, thick-walled telescopic handle with aluminum tube and ergonomic handpiece.

The attached snap connection provides a secure link to all necessary attachments.

Paint Tray 'Small' (15 x 30 cm)



Paint Tray 'Small', for use with the SAICOS Flat Brush and Universal Roller 'Small'. Tray inserts can be ordered separately in 5-piece sets.

Product	ltem Number
Paint Tray	0950 227
5x Tray Insert	0950 228

Paint Tray 'Large'



Large Paint Tray, for use with the SAICOS Rollers and SAICOS Flat Brush. Tray inserts can be ordered separately in 5-piece sets.

Product	ltem Number
Paint Tray	0950 229
5x Tray Insert	0950 230





Care Instruction oiled wooden floors





Care Instruction lacquered wooden floors

Maintenance for all surfaces

solvent-free, perfect for wood, design floors, tiles, stones, ...







$1 l = approx. 700 m^2$











Ecoline Wash Care Concentrate for all surfaces

Can Size	ltem Number
0,125 L	8101Eco 101
1 L	8101Eco 409
5 L	8101Eco 610
10 L	8101Eco 710

For **solvent-free** damp cleaning of **all** wood and cork floors and **all other wipeable** floors.

Made of plant soaps and natural care ingredients, it cleans and protects without streaks.

Ecoline Wash Care protects against recontamination and is especially kind to skin.

Very well-suited for laminate floors.

Application with Ecoline Maintenance Set (8108Eco).

Maintenance for all surfaces

solvent-free, perfect for wood, design floors, tiles, stones, ...



concentrate & spray

Ecoline Magic Cleaner for all surfaces

Can Size	Item Number
0,125 L	8125Eco 101
1 L	8125Eco 409
5 L	8125Eco 610
10 L	8125Eco 710
Spray (ready for use)	
1 L	8126Eco 417

Save yourself the hard work of sanding worn down surfaces. *Ecoline Magic Cleaner* – the perfect solvent-free solution!

Suitable for intensive cleaning of **all wooden surfaces** and all other surfaces such as PVC, linoleum and tile.

Removes nicotine, fat and dirt, e.g. in the kitchen and bathroom. Suitable for cleaning machines. 1 liter is sufficient for approx. 10 liter of water.

Application with Ecoline Maintenance Set (8108Eco).



Care for oiled surfaces

to make correct care a child's play





regenerative care

$1 l = approx. 100 m^2$











1 l = approx. 200 m















Wax Care

Can Size	ltem Number
0,3 L	8100 180
1 L	(Item Number) 404
10 L	(Item Number) 715

SAICOS Wax Care is a naturally based fluid cleaning and care product for wood. It is specially developed for wood and cork floors with oiled surfaces, as well as furniture (desk and table surfaces) and other wood surfaces.

For freshening and caring for heavily worn wood and cork floors. Effortlessly removes stubborn stains, water marks, marks from rubber soles, etc. Regular care protects, regenerates and freshens the surface.

Application with SAICOS Telescope-Maintenance Cloth (8189).

8100 Colourless transparent

for wood.

8111 White transparent

Ecoline Wax Care

Can Size	ltem Number
11	(Item Number) 409
10	(Item Number) 710
Spray (ready for use)	
11	(Item Number) 417

Ecoline Wax Care is a naturally based,
solvent-free fluid cleaning and care product

It is specially developed for wood and cork floors with **oiled surfaces**, as well as furniture (desk and table surfaces) and other wood surfaces.

For freshening and caring for heavily worn wood and cork floors. Regular care protects, regenerates and freshens the surface.

Application with Ecoline Maintenance Set-(8108Eco).

Wax Care / Spray

8119Eco / 8129Eco Colourless transparent

8111Eco White transparent

All-in-one package for oiled surfaces

cleaning or cleaning & care - the choice is yours



complete set incl. cloths





complete set incl. cloths



Ecoline Floor Care Set for oiled surfaces

Product	Item Number
Set	8310Eco

We have combined everything you need to care for your wood floor in a handy set.

1. Cleaning:

Ecoline Wash Care
For solvent-free wet cleaning
of all wood and cork floors and
all other wipeable floors.
1 liter of concentrate

2. Care and protection:

Ecoline Wax Care
For freshening and caring of
heavily used wood and cork floors.
1 liter colourless

Handy accessories:

application cloths instructions for use

Ecoline Floor Clean & Care Set for oiled surfaces

Product	ltem Number
Set	8311Eco

We have put together everything that you need for to **clean and care** for your wood floor in a practical set:

1. Cleaning:

Ecoline Magic Cleaner
For intensive cleaning of all wood surfaces and all other surfaces.

1 liter of concentrate

2. Care and protection:

Ecoline Wax Care
For freshening and caring of
heavily used wood and cork floors.
1 liter colourless

Handy accessories:

application cloths instructions for use

Professional care for oiled surfaces

Initial maintenance and renovation





refreshing

$1 L = approx. 100 m^2$









Wash Care Oil for oiled and waxed surfaces

Can Size Item Number

1 L (Item Number) 404

Especially for oiled and waxed parquet.

One cap size for 1m².

Apply equally with the SAICOS Telescope-Maintenance Cloth on the cleaned floor and let dry.

Frequency of maintenance:

Annually (commercial sector) or according to demand.

Application with SAICOS Telescope-Maintenance Cloth (8189).

8145 Satin matt colourless

8145M Matt colourless







recoating and refreshing

$1 L = approx. 100 m^2$









Professional Care Oil for pre-oiled surfaces

Can Size

1 L (Item Number) 404

Item Number

For the final coating of pre – oiled wood floors (hardwood and softwood), parquet, planks, wood – block pavings and industrial parquet.

Put the SAICOS Professional Care Oil on the floor and apply equally with a spatula. Buff the treated surface until even appearance with one- or multidisc rotary machine (white pad) after max. 30 min.

Frequency of maintenance:

Annually (commercial sector) or according to demand.

81395 Satin matt colourless

8139W White transparent satin matt 8139M Matt colourless





Removes water and reaction stains

highly effective special product





Stain Remover

Can Size	Item Number
0,5 L	8158 217

SAICOS Stain Remover is a highly effective special product for removing water as well as reaction spots (e.g. oxidation) on oiled oak surfaces. The gel-like texture makes it easy to apply and has a particularly intensive effect.

especially for oak

0.5 L = approx. 5 m²

Maintenance & renovation for lacquered surfaces

for renovation and renewal of your hard-wearing surfaces



$1 L = approx. 100 m^2$

Ecoline MultiTop Lacquer Polish – for lacquered surfaces

Can Size	Item Number
1 L	(Item Number) 409

Especially for lacquered floors. For renovation and renewal of your hard-wearing lacquer surfaces.

Application with the SAICOS Telescope-Maintenance Cloth (8189).

8152
Matt
colourless

8153 Satin Matt colourless







low-solvent: VOC < 5%

1 I = 10 I water

Ecoline Refresher – for lacquered surfaces

Can Size	Item Number
1 L	8106Eco 409
5 L	8106Eco 610
10 L	8106Eco 710

Low-solvent care and regeneration concentrate for **lacquered** wood and bamboo surfaces.

It retains the beautiful, clear look of your lacquered surfaces, whilst regenerating them and keeping them looking fresh. Surfaces treated with this product are dirt-repellent and extremely durable.

Application with the Ecoline Maintenance Set (8108Eco).

Cleaning, care & accessories

to make correct care a child's play



2parts - complete set

Telescope-Maintenance Cloth

Product	Item Number
Telescopic handle & 1 wiper	8189
Replacement cloth	
1 cloth	8190

Extractable telescopic handle (1,05 - 1,85 m) with special-cloth suitable for:

- SAICOS Wax Care (8100 / 8111)
- SAICOS Wash Care Oil (8145 / 8145M / 8144)
- Ecoline MultiTop Lacquer Polish (8152Eco / 8153Eco)



3parts - complete set

Ecoline Maintenance Set

Product	Item Number
Telescopic handle & 2 wipers	8108Eco
Replacement cloths	
2 pieces	8188Eco

Telescopic handle (0,90 - 1,40 m) including 2 special wipers.

Especially developed for these maintenance products:

- Ecoline Wash Care (8101Eco)
- Ecoline Magic Cleaner (8125Eco)
- Ecoline Wax Care (8119Eco / 8111Eco)
- Ecoline Refresher (8106Eco)

Clean & care of oiled wood surfaces



Fields of application:

For all wooden and cork floors with waxed / oiled surface and all other floors such as PVC, linoleum, ceramic, tiles \dots

Very well suited for laminate floors.

Also for furniture and other interior wood with waxed / oiled or lacquered surface.

Recommended application:



» Dilute the concentrate with water (3 caps with approx. 5 l of water).



- » We recommend the application with Ecoline Maintenance Set 8108Eco.
- » Make sure that the wiping cloth is wrung out carefully to ensure damp cleaning.



- » Wipe dry if required.
- » To remove particularly stubborn stains, as well as for occasionally freshening and caring of oiled wood and cork floors, furniture and interior woods, we recommend our Wax Care.



- » Heavily worn down oiled floors can also be renovated with Hardwax-Oil.
- » Please consider our current technical data sheets.



Fields of application:

Intensive cleaning of all waxed, oiled or lacquered surfaces. Also for all other surfaces such as PVC, Linoleum, ceramic, tiles, natural stone ...

Easy removal of nicotine, grease and dirt films in bathroom and kitchen.

Recommended application:



- » Dilute the concentrate 1:10 with water (e.g. 0.5 | with 5 | of water).
- » Put the dilution evenly on the surface with our Ecoline Maintenance Set, wiper or cloth.
- » Do not pour on the surface and do not leave any puddles.



- » Allow to absorb for 5 20 minutes.
- » Re-treat dried areas during this time.



- » Remove any loosened dirt thoroughly with a damp *Ecoline Maintenance Set*, clean wiper or cloth.
- » Wipe 2 3 times with fresh water and a damp cloth. Wipe dry.
- » Repeat the application if necessary.



- » Do not apply on untreated wood / cork surfaces, as this may hamper a subsequent coating.
- » Please consider our current technical data sheets.



Clean & care of oiled wood surfaces



Fields of application:

Especially for wooden and cork floors with waxed / oiled surface, as well as furniture (work and table tops) and other wooden surfaces.

Recommended application:



- » Clean the surfaces to be treated with Ecoline Wash Care.
- » Shake Wax Care well before use.



» Pour the quantity of one cap (for approx. 1-2 m²) on the surface and spread evenly with SAICOS Telescope-Maintenance Cloth (SAICOS Wax Care) or Ecoline Maintenance Set 8108Eco (Ecoline Wax Care). Alternatively the material can be spread evenly with a cloth when having small areas.



- » Allow to dry.
- » No visible contact points to non-treated surfaces.



» Please consider our current technical data sheets.





Fields of application:

Especially for oiled and waxed wood surfaces. Also well suited for furniture and other interior wood.

Recommended application:



- » Clean the surfaces to be treated with Ecoline Magic Cleaner.
- » Sand with a green pad if necessary.
- » Remove sanding dust thoroughly with a dry cloth and vacuum cleaner.
- » The wood surface must be dry and clean.



» Before use, allow can to acclimate to room temperature and shake well.



- » Apply one cap (for approx. 1 m²) onto the surface.
- » Rub evenly with the SAICOS Telescope-Maintenance Cloth and let it dry.
- » Do not leave any puddles, to avoid an irregular surface.



- Ensure that windows are open during and after application.
 Oxidative drying ensure good ventilation.
- » Please consider our current technical data sheets.

Clean & care of oiled wood surfaces



Fields of application:

For wood floors made of hard or soft woods, parquet, planks, wood block and industry parquet. Suitable for all European wood species, exotic woods and smoked oak.

Recommended application - repair & renovation:



- » Sand with a green pad if necessary.
- » Remove sanding dust thoroughly with a dry cloth and vacuum cleaner.
- » The wood surface must be dry and clean.



» Shake well before use - do not dilute.



» Apply thin and evenly once or twice with a white pad or cloth.



- » Ensure that windows are open during and after application for ventilation.
- » Please consider our current technical data sheets.



Fields of application:

All kinds of indoor wood flooring: parquet, solid wood floors, strip parquet, veneer wood ... All kinds of cork floors: parquet, cork tiles ...

Also for other high-wear wood surfaces: counter and table tops, furniture and other interior wood – also recommended for children's toys and other wood objects. Ideal for use in rooms with high humidity such as bathrooms and kitchens.

Recommended application - Repair & Renovation:



» Clean the surfaces to be treated with Ecoline Magic Cleaner.



- » The wood surface must be dry and clean.
- » Sand with a green pad if necessary.
- » Remove sanding dust thoroughly with a dry cloth and vacuum cleaner.



- » Stir well do not dilute.
- » Apply thinly and evenly once or twice with a white pad or cloth.



- Ensure that windows are open during and after application.
 Oxidative drying ensure good ventilation.
- » Please consider our current technical data sheets.

Clean & care of lacquered wood surfaces



Fields of application:

For all wooden and cork floors with lacquered surface and all other floors such as PVC, linoleum, ceramic, tiles ...

Very well suited for laminate floors.

Also for furniture and other interior wood with waxed / oiled or lacquered surface.

Recommended application:



» Dilute the concentrate with water (3 caps with approx. 5 l of water).



- » We recommend the application with Ecoline Maintenance Set 8108Eco.
- » Make sure that the wiping cloth is wrung out carefully to ensure damp cleaning.



» Wipe dry if required.



» Please consider our current technical data sheets.

Clean & care of lacquered wood surfaces



Fields of application:

Intensive cleaning of all lacquered surfaces. Also for all other surfaces such as PVC, Linoleum, ceramic, tiles, natural stone \dots

Easy removal of nicotine, grease and dirt films in bathroom and kitchen.

Recommended application:



- » Dilute the concentrate 1:10 with water (e.g. 0.5 | with 5 | of water).
- » Put the dilution evenly on the surface with our *Ecoline Maintenance Set*, wiper or cloth.
- » Do not pour on the surface and do not leave any puddles.



- » Allow to absorb for 5 20 minutes.
- » Re-treat dried areas during this time.



- » Remove any loosened dirt thoroughly with a damp Ecoline Maintenance Set, clean wiper or cloth.
- » Wipe 2 3 times with fresh water and a damp cloth. Wipe dry.
- » Repeat the application if necessary.



- » Do not apply on untreated wood / cork surfaces, as this may hamper a subsequent coating.
- » Please consider our current technical data sheets.

Clean & care of lacquered wood surfaces



Fields of application:

Especially for *Ecoline* lacquered flooring made of wood and bamboo. Also well suited for furniture and other interior wood (lacquered surfaces).

Recommended application:



Clean the surfaces to be treated with Ecoline Wash Care.



 Dilute Ecoline Refresher Concentrate 1:10 with water (e.g. 0.5 | with 5 | of water).



 Spread evenly on the surface with a damp wiper (Ecoline Maintenance Set).



- » Allow to dry.
- » Please consider our current technical data sheets.

Clean & care of lacquered wood surfaces



Fields of application:

Especially for *Ecoline* lacquered flooring made of wood and bamboo. Also well suited for furniture and other interior wood (lacquered surfaces).

Recommended application:



- » Shake well before use.
- » Clean the surfaces to be treated with Ecoline Wash Care or in case of heavy soiling / worn out surface, clean with Ecoline Magic Cleaner.
- » Sand with a *green pad* if necessary. Remove sanding dust thoroughly with a dry cloth and vacuum cleaner.



- » Spread even and sufficiently on the cleaned and dry floor with the SAICOS Telescope-Maintenance Cloth - do not process by machine.
- » Too little application prevents the smooth leveling. Avoid puddles, splashes and drops.
- » Spread evenly do not polish.
- » Treat larger surfaces in sections. It must not have been dried between sections.
- » Last application should be done in direction of wood grain.



» Please consider our current technical data sheets.

Clean & care of laminate, vinyl and design floors



Fields of application:

Very well suited for regular cleaning of laminate, vinyl and design flooring. Also for all other wipeable surfaces such as PVC, linoleum, ceramic, tiles...

Recommended application:



» Dilute the concentrate with water (3 caps with approx. 5 l of water).



- » We recommend the application with Ecoline Maintenance Set 8108Eco.
- » Make sure that the wiping cloth is wrung out carefully to ensure damp cleaning.



» Wipe dry if required.



» Please consider our current technical data sheets.

Clean & care of laminate, vinyl and design floors



Fields of application:

Intensive cleaning of laminate, vinyl and design floors. Also for all other surfaces such as PVC, Linoleum, ceramic, tiles, natural stone ... Easy removal of nicotine, grease and dirt films in bathroom and kitchen.

Recommended application:



- » Dilute the concentrate 1:10 with water (e.g. 0.5 l with 5 l of water).
- » Put the dilution evenly on the surface with our Ecoline Maintenance Set, wiper or cloth.
- » Do not pour on the surface and do not leave any puddles.



- » Allow to absorb for 5 20 minutes.
- » Re-treat dried areas during this time.



- » Remove any loosened dirt thoroughly with a damp *Ecoline Maintenance Set*, clean wiper or cloth.
- » Wipe 2 3 times with fresh water and a damp cloth. Wipe dry.
- » Repeat the application if necessary.



» Please consider our current technical data sheets.



All care products at a glance

the right solution for all floors







Ecoli	ne W	ash	Care
-------	------	-----	------

Ecoline Magic Cleane

Ecoline Wax Care

	Econne wash care	Magic Cleaner	Econne wax care	
low-solvent/solvent-free	VOC free	VOC free	VOC free	
Coating	all	all	oil	:
Wood and bamboo floors	✓	✓	✓	
Table and desk surfaces	✓	✓	✓	
Furniture	✓	✓	✓	
Ceiling and wall panels	~	~		
Toys	✓	✓		
Laminate, PVC, others	*	✓		
Product type	concentrate	concentrate and spray	ready-to-use and spray	
Available package sizes	1 L 5 L 10 L	1 L 5 L 10 L	1 L 10 L	
Mix ration with water / application quantity	3 caps with 5 l	1:10	1 cap for approx. 1-2 m²	
Application interval private	monthly (or as required)	annually (or as required)	2x per year (or as required)	
Application interval objects	weekly (or as required)	2x per year (or as required)	monthly (or as required)	
Application	1	1		

approx.

700 m²

approx.

100 - 150 m²

approx.

200 m²

Coverage (m² per 1 liter)









Ecoline

Refresher



AND THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TWO IS NAMED IN COLUMN TWO I					
	Wax Care	Professional Care Oil	Wash Care Oil		

	oil	oil	oil		
	✓	✓	✓		
:	✓	✓	✓		
	✓	✓	✓		
-					
		✓	~		
		√ √	✓		
			<i>*</i>		



Ecoline MultiTop Lacquer Polish





			VOC <5%	VOC free
oil	oil	oil	lacquer	lacquer
✓	✓	✓	✓	√
✓	√	✓	✓	✓
✓	✓	✓	✓	✓
	~	~		
	✓	✓		
ready-to-use	ready-to-use	ready-to-use	concentrate	ready-to-use
0,3 L 1 L 10 L	1 L	1 L	1 L 5 L 10 L	1 L
1 cap for approx. 1 m²	1 L = approx. 100 m ^a	1 L = approx. 100 m ^a	0,5 l with 5 l	1 L = approx. 100 m ^a
2x per year (or as required)	annually (or as required)	annually (or as required)	2x per year (or as required)	annually (or as required)
monthly (or as required)	annually (or as required)	annually (or as required)	monthly (or as required)	annually (or as required)
			1	
approx. 100 m²	approx. 100 m²	approx. 100 m²	approx. 200 m²	approx. 100 m²













» Where can I buy SAICOS products?

You can find our products in specialist shops or at various online suppliers. To find one of our partners, please use our dealer search.

» Why does the same transparent paint appear so differently in colour on different woods? The colour result depends on several factors: in addition to the wood type and texture, the wood sanding, for example, is also decisive. We recommend a trial coating on the original wood to get a precise preview of the later colour shade.

» Can I mix the colours with each other?

Yes, the colours of the individual product families can be mixed with each other. (Please do not mix different product families with each other).

» What is the shelf life of the product?

Please refer to our Technical Data Sheets for information on storage stability and shelf life.

» How economical are the colours?

The coverage of a product depends on the wood type and the wood texture. For more detailed information, please refer to our Technical Data Sheets.

» What can I use to thin a product?

Our coatings are ready to use and do not need to be thinned. However, if this is still desired, oil-based coatings can be thinned with our *SAICOS Brush Cleaner*. Water-based coatings can be diluted with water (with reservation only).

» How do I clean my tools such as brush, roller or paint tray?

Water-based products can be washed out with water. Oil-based products are best cleaned with our SAICOS Brush Cleaner.

» Where does the smell come from when the oils dry? Do I have to worry?

No, because our systems all have DIBT approval and are classified as harmless. During drying, a slight odour is produced by the natural substances used. Please ensure good air circulation during and after coating.

» The floor turned out too dark after the final coating. How can I make it lighter when the coating is already completely dry?

Unfortunately, the floor has to be completely sanded and recoated.

» I have a floor with a bevel and would like to coat it with SAICOS Ecoline Oil Ground Coat. How should I proceed?

Please precoat the bevels with the SAICOS Floor Brush and then level the coating with a white pad.

You ask, we answer!

» The coloured primed floor has become stained after the application of SAICOS Premium Hardwax-Oil. What happened, what to do?

In this case, the drying time of the primer was not observed or the climatic conditions did not match our recommendations. The floor must be completely sanded and then recoated. In this case, we recommend the use of the 2K Hardener Additive.

» The SAICOS Premium Hardwax-Oil surface is not yet dry after the specified drying time.
What should I do?

The SAICOS Premium Hardwax-Oil will dry completely in any case. Make sure there is sufficient ventilation: Open all windows and doors. If necessary, a fan can be placed in the doorway.

» Is there a rule of thumb when a SAICOS Premium Hardwax-Oil floor can be walked on and when furniture can be placed?

Drying depends on many factors such as ventilation and temperature, but usually takes between 3 - 5 hours. After 24 hours, the first furniture can be carefully placed. The surface is fully hardened after approx. 4 days. With the addition of *Hardener 2K*, the drying and curing time is shortened.

- » I have roller marks after applying SAICOS Premium Hardwax-Oil. What should I do? In this case, the floor must be sanded and recoated after complete drying. If these are not too strong, you can also pad the floor marone, then polish on the SAICOS Professional Care Oil evenly and thinly with a white pad.
- » If I use the Ecoline Oil Ground Coat, , how many coats of SAICOS Premium Hardwax-Oil or SAICOS MultiTop lacquer is needed?

With the SAICOS Premium Hardwax-Oil, one coat is required. With the SAICOS Ecoline $MultiTop^{Plus}$ System it is 2 coats (with the varnish the surface must be sanded with a green pad after drying of the first lacquer coat).

- » My floor is pre-oiled by the supplier. What do I use to apply a final coat? After previous cleaning sand with a green pad, roll on SAICOS Premium Hardwax-Oil once thinly or pad on SAICOS Ecoline Hardwax-Oil once thinly.
- » Is the SAICOS Ecoline Oil Ground Coat a sole coat?

No. SAICOS Ecoline Oil Ground Coat is not sufficient as a sole coat, as the pigments must be protected from running off. For the final coat we recommend SAICOS Premium Hardwax-Oil, SAICOS Ecoline Hardwax-Oil or our SAICOS Ecoline MultiTop^{Plus} Lacquer System (sanding with green pad necessary).

» The coloured SAICOS Ecoline Oil Ground Coat has turned out too light. How can I make it darker?

For a more intensive, darker result, you can apply the SAICOS Ecoline Oil Ground Coat a second time after it has dried completely or add up to 3% of the SAICOS Ecoline Oil Ground Coat to the SAICOS Premium Hardwax-Oil.

- » Can I change the gloss level of SAICOS Premium Hardwax-Oil by polishing or similar?
 No. We offer 4 different degrees of gloss of our SAICOS Premium Hardwax-Oil in this respect.
- » I don't like the gloss level of SAICOS Premium Hardwax-Oil. What can I do? Sand with a sanding grid or multi-hole pad and then roll on thinly again to the desired degree of gloss.
- » What is the difference between SAICOS Premium Hardwax-Oil and SAICOS Ecoline Hardwax-Oil?

The solids and solvent content as well as the method of application. SAICOS Premium Hardwax-Oil is applied twice thinly with the oil/wax roller. SAICOS Ecoline Hardwax-Oil is applied twice with a single-disc machine using a white or beige pad.



Our application advice is given to the best of our knowledge and based on experiments, but should only be treated as a non-binding guide. You must still check that the products delivered are suitable for the intended purpose. As we have no control over the application and processing of our products, the user bears full responsibility. The previous product informations shall be deemed invalid following publication of a new brochure. Changes reserved. All images of our product colour palettes are non-binding and may deviate from the original colour.

For more information, please read our current technical data sheets. The protection of your personal data is very important to us. You can find our privacy policy on www.saicos.de.

Care instructions for sealed parquet and wood flooring in accordance with DIN 18356. To ensure a good atmosphere in the room and to preserve your wood floor, we recomend a room temperature of 20-25 °C and a relative humidity of 55-60%. For more information, please read our current technical data sheets.

Photos: SAICOS COLOUR GmbH / Shutterstock, Inc. / 123RF, Adobe



SAICOS COLOUR GmbH

Carl-Zeiss-Str. 3
D-48336 Sassenberg
♣ +49 2583 3037-0
♣ +49 2583 3037-10
info@saicos.de
www.saicos.de

