

# Professional Care Oil

Technical Data Sheet  
October 2022  
Page 1/1



- » *initial care*
- » *extremely durable*
- » *dirt-resistant - easy-care*

## Product characteristics:

*SAICOS Professional Care Oil* is a surface protection for wooden floors, based on natural oils, for private living and public areas. Additional surface protection, initial care or refresher for all oiled/waxed wooden floors. Microporous, water-repellent, dirt-resistant, hardwearing. Easy to clean. The partial renovation of highly used or damaged areas is possible. Slip Resistant R9.

## Colour:

**8139S** Colourless, Satin Matt

**8139M** Colourless, Matt

## Fields of application:

For wood floors made of hard or soft woods, parquet, planks, wood block and industry parquet. Suitable for all European wood species, exotic woods and smoked oak. In case of unknown species, please make a test coating on an original sample.

## Preparation:

Surface must be clean and dry.  
Shake well before use, do not thin.

## Application:

Put some *SAICOS Professional Care Oil* on the floor and spread crosswise thinly and evenly with a double spatula. Within 30 minutes equalize cloudless with an one disc machine with white or beige pad. Do not leave standing puddles of material. Edges edit by hand. Ensure good ventilation.

**Drying time:** min. 8 hours (depending on temperature and air humidity).

**Coverage per liter:** 100 m<sup>2</sup>/ltr.

## Best processing temperature:

Material temperature +15 °C - +25 °C  
Room temperature +15 °C - +25 °C  
Rel. humidity 50 - 60 % ideal  
Floor temperature min. 8 °C

**Cleaning of tools:** with [SAICOS Brush Cleaner](#).

## Storage:

At least 5 years in sealed container. The liquid product is not susceptible to frost.

## Physical properties:

**Density:** 0,88 - 0,95 g/cm<sup>3</sup>

**Odour:** faint/ mild, natural oils

**Flashpoint:** > 63 °C according to DIN 53213.

## Safety Instructions – First Aid:

Keep out of the reach of children. Do not fill into food, beverage or other containers used for foodstuffs. Wash out any product-soaked rags immediately or store in an airtight container (danger of combustion). The dried coating is normally inflammable acc. to EURO norm EN 13501 (DIN 4102 B2). Safety data sheet available on request.

**8139S:** EU limit for clear coatings and stains (cat. A/e): 400 g/l (2010). *SAICOS Professional Care Oil Satin matt* contains max. 400 g/l VOC.

**8139M:** EU limit for one component coatings (Kat. A/i): 500 g/l. *SAICOS Professional Care Oil Matt* contains max. 500 g/l.

Our application advice is provided to the best of our knowledge and based on experiments, however, applies only as a non-binding recommendation and does not exempt you from testing the products supplied by us as to their suitability for the intended purpose. Since the application and processing of the products is beyond our control, the responsibility rests solely with the user. With publishing a new technical data sheet the previous loses its validity.

## SAICOS COLOUR GmbH

Carl-Zeiss-Str. 3

D-48336 Sassenberg

☎ +49 2583 3037-0

☎ +49 2583 3037-10

info@saicos.de

[www.saicos.de](http://www.saicos.de)