Wash Care Oil

Technical Data Sheet July 2022 Page 1/1





- » insensitive to dirt, water-repellent, hardwearing
- » saliva and sweat resistant
- » healthy and breathable
- » surface easy to clean
- » suitable for hot water underfloor heating

Product characteristics:

SAICOS Wash Care Oil, the liquid wood care product made from natural ingredients. For the maintenance of heavily used wood and cork surfaces. Anti-Slip R9.

Colours:

8145 Satin Matt, colourless8145M Matt, colourless

Fields of application:

Especially for oiled and waxed wood surfaces. Also well suited for furniture and other interior wood.

Preparation: Clean the surfaces to be treated with <u>Ecoline Magic</u> <u>Cleaner</u> – the perfect solution for worn down surfaces. For further information please read the technical data sheet.

Application:

Before use, allow the container to acclimate to room temperature and shake well. Put the amount of one capful (for approx. 1 m²) on the cleaned floor and spread evenly with the <u>SAICOS Telescope-Maintenance Cloth</u> and leave to dry. Do not leave puddles to avoid an uneven surface.

Removal of stubborn stains:

pour small quantity of *SAICOS Wash Care Oil* on the floor and rub stain with a rag. Never use steel wool, filament mop (microfibre) or abrasive cleaners!

Drying time:

Approx. 3 hours. Ensure that windows are open during and after application. Oxidative drying – ensure good ventilation. Remove any surplus with an absorbent cloth or machine with a white pad.

Number of treatment: annually (or as required)

Best processing temperature: Between 8 °C and 35 °C.

Coverage per liter: 1 Liter = approx. $100 \text{ m}^2 / 1 \text{ cap for approx. } 1 \text{ m}^2$

Storage: Can be stored for at least 5 years in closed containers. The liquid product is not at risk of frost - to restore good spreadability after exposure to frost, store at room temperature for a few hours and shake well.

Physical characteristics:

Density: 0,75 - 0,85 g/cm³

Odour: weak / mild (after natural vegetable oils and waxes), odor-less after drying. **Flashpoint:** 28 °C

Safety Instructions - First Aid:

Keep out of the reach of children. Do not fill into containers normally used for food and drink. Flammable liquid and vapour. No smoking. Normally inflammable after drying. Wash out any product-soaked rags immediately or store in an airtight container (danger of combustion). May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. Ground and bond container and receiving equipment. Use explosion-proof electrical equipment. Use non-sparking tools. Avoid breathing vapours. Take action to prevent static discharges. Use only outdoors or in well ventilated areas. Avoid release to the environment. Wear protective gloves and eye/face protection. IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water (or shower). IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER / doctor if you feel unwell. Do NOT induce vomiting. In case of fire: Use extinguishing powder or sand to extinguish. Store container tightly closed in a well-ventilated place. Keep cool. Keep locked up. Dispose of contents/container to industrial incineration plant. Contains: hydrocarbons, C9-C10, n-alkanes, isoalkanes, cycloalkanes < 2 % aromatics.

UN1263

Our application advice is provided to the best of our knowledge and based on experiments, however, applies only as a non-binding recommendation and does not exempt you from testing the products supplied by us as to their suitability for the intended purpose. Since the application and processing of the products is beyond our control, the responsibility rests solely with the user. With publishing a new technical data sheet the previous loses its validity.

SAICOS COLOUR GmbH

Carl-Zeiss-Str. 3

D-48336 Sassenberg

4 +49 2583 3037-0

♣ +49 2583 3037-10

info@saicos.de

www.saicos.de